



Mobile Hose Reels

- High capacity and efficiency, ideal for rapid deployment.
- Enhanced safety and control with disk brakes to both wheels.
- Durable and corrosion resistant – Zinc plated and finished with a red powder coat.
- Cast aluminium wheels with rubber tyres for improved handling.
- Enhanced visibility with reflective markings.
- AFNOR approved, CNPP audited – NF-377.

The AFNOR approved TYP.940.1 is widely used throughout France, supporting firefighters with the rapid deployment of 70mm lay flat fire hose and dividing breaching.

Cast aluminium wheel hubs with heavy duty rubber wheels are stabilised by an 'always on' braking system benefiting from disk brakes on each wheel hub.



MATÉRIELS
SAPEURS POMPIERS
245-002
www.marque-nf.com





- AFNOR approved, CNPP audited – NF-377.
- Capacity for 200m of 70mm lay flat hose, in 5 x 40m lengths.
- Disk brakes to both wheels.
- Zinc plated and red powder coat on all steel parts.
- Cast aluminium wheels with rubber tyres for improved handling.
- Reflective markings to illuminate the reel in darker conditions.

Each Mobile Hose Reel is tested to a fully laden weight of 250kg and is type tested in accordance with the AFNOR standard.

Since its launch, the **+Collins Youldon** wheeled Mobile Hose Reel has become a firefighter-preferred piece of kit due to the large rubber wheels and disk brakes to each wheel. These disk brakes stabilise the reel when fully loaded with hose to give firefighters confidence in its performance.

Key stats	mm / kg
Width	946
Height	1,230
Depth	812
Unladen weight	70.5

Warranty

Our products benefit from a 12-month manufacturer’s warranty. Extended warranty available.

Service life

Due to the advanced design and manufacturing techniques, a well serviced and maintained reel could continue running for many years.

Spare parts

These are available from Supply Plus as needed. Optional extras are also available – contact us for further details.

Made in the UK

Supply Plus is headquartered in Cambridge, UK, in our 6,000m² (64,000ft²) facility.

